

Infinity Pendant Light Fitting

INSTRUCTION MANUAL

Safety Warnings

- This product is only suitable for connection to a 240V~50Hz supply in accordance with current IEE wiring regulations, and should be installed in accordance with local building regulations. It is for domestic ceiling use only, and is not suitable for a bathroom location.
- Before installing your light fitting always switch off the mains supply and remove the appropriate fuse or switch off the appropriate circuit breaker before commencing installation.
- This is a Class II product and **must NOT** be connected to Earth. The terminal blocks are supplied according to requirements of the fitting.
- Never fit bulbs of a higher wattage than those specified on the label as these may damage the fitting).
- If you are in any doubt about your competence please consult a qualified electrician.
- **This product contains very delicate parts** – be careful during handling and maintenance to avoid breakage. Spare glass balls are available - please contact your retailer or call our service team on 0333 00 333 08.
- If any modification is made it will invalidate the warranty and may render the product unsafe.

Care Information

Allow 10 minutes to cool before replacing, adjusting or cleaning.

Clean with a dry cloth only. Do not use liquid or abrasive cleaners on this product.

Assembly/ User Instructions

Before you start

Please read these instructions carefully before fitting and retain for reference. Check the packaging and make sure that you have all the required parts. Follow each assembly step in order to prevent incorrect assembly. Ensure that the product is fully assembled as illustrated before use.

The light pack contains:

Light fitting.	18x B rod
Terminal connection block(s).	6x C rod
Fixing pack.	3x D rod
1x A rod	28x glass balls

The following tools may be required:

Selection of cross and flat head screwdrivers.
Electric drill and assorted drill bits.
Wire strippers.
Electrical insulation tape.

These assembly diagrams are intended as a guide – if in doubt consult a qualified electrician.

1. Decide on the position of the light fitting or remove existing light fitting. Note the position of the electrical connections, and ensure there is a solid mounting surface, preferably a wooden joist or joist bridge, to support the weight of the light fitting.
2. If you want to reduce the overall length of the fitting it is essential that this is done before the fitting is mounted to the ceiling, or connected to the mains supply. Push the clutch up to release the support wire, then pull it through the ceiling cup until the desired length is reached, then release the clutch ensuring the wire is gripped. The cable must now be shortened and the excess cable cut and re-connected to the terminal block. Feed the cable up through the plastic bush and form a loop above the ceiling cup, moving the figure of 8 cable restraint down the exposed cable.
NOTE: The electric cable must always be longer than the support wire to prevent strain being placed on the cable. If you are unsure about your ability to do this, we recommend you contact a qualified electrician.
3. Remove the two side screws (4) and retain for re-use. Use the fixing bracket (1) as a template to mark the screw holes. Make the screw holes and secure to the ceiling with appropriate screw fixings (2).
4. Support your fitting and connect the house wiring to the terminal block (3) – see expanded wiring details below.
NOTE: This is a Class II fitting and must NOT be earthed. Any loose terminal blocks – not secured to ceiling cup – should always be covered with 2 layers of good quality insulation tape.
5. Secure the ceiling cup over the bracket by using the screws (4) removed in Point 3.



Assembly/ User Instructions Continued

- Fit the bulbs (5). **NOTE: Never fit bulbs of a higher wattage than those specified on the label, as these may cause overheating and damage the fitting.**
- Fit the rods (See inset 6) by screwing them into the body of the lamp - following the diagrams below. Start with Level 5 - D rods, then fit Level 4 - C rods, followed by Levels 3-1 - B rods. Screw Rod A into the underside of the fitting.
- Fit the glass balls (7), taking care as these are very delicate. Again, starting from the lowest point of the fitting, screw the balls onto the rods, working around and upwards so the glass hangs correctly.
- Turn on the power and test.

NO	A	B	C	D	E	FG	H	I
Qty	1	18	6	3	28	22	1	1

