


# Hadassa Pendant Light Fitting

## INSTRUCTION MANUAL

### Safety Warnings

- This product is only suitable for connection to a 240V~50Hz supply in accordance with current IEE wiring regulations, and should be installed in accordance with local building regulations. It is for domestic ceiling use only, and is not suitable for a bathroom location.
- Before installing your light fitting always switch off the mains supply and remove the appropriate fuse or switch off the appropriate circuit breaker before commencing installation.
- This fitting is a Class II, Double Insulated product  and does not require an Earth. Live or Neutral must not be connected to Earth.
- Never fit bulbs of a higher wattage than those specified on the label (as these may cause overheating and damage the fitting).
- If the mains cable becomes damaged it must only be replaced by a technically competent, qualified person.
- Allow 10 minutes to cool before replacing, adjusting or cleaning. Clean with a dry cloth only. Do not use liquid or abrasive cleaners on this product.
- If you are in any doubt about your competence please consult a qualified electrician.
- If any modification is made it will invalidate the warranty and may render the product unsafe.

### Care Information

Allow 10 minutes to cool before replacing, adjusting or cleaning.  
Clean with a dry cloth only. Do not use liquid or abrasive cleaners on this product.

### Assembly / User Instructions

#### Before you start

Please read these instructions carefully before fitting and retain for reference. Check the packaging and make sure that you have all the required parts. Follow each assembly step in order to prevent incorrect assembly.

#### The Light pack contains:

Light fitting  
Fixing pack

#### The following tools may be required:

Selection of cross and flat head screwdrivers.  
Electric drill and assorted drill bits.  
Wire strippers.  
Electrical insulation tape

**These assembly diagrams are intended as a guide – if in doubt consult a qualified electrician.**

1. Decide on the position of the light fitting or remove existing light fitting. Note the position of the electrical connections, and ensure there is a solid mounting surface, Preferably a wooden joist or joist bridge, to support the weight of the light fitting.
2. Unscrew the side screws (B) from the ceiling cover and detach the ceiling bracket (D) from the fitting. Keep the side screws safe for refitting later.
3. Attach the ceiling bracket (D) to the ceiling using the screws provided. Ensure there is a joist at the point of fixing to support the weight of the product. Take care to avoid damaging any concealed wiring and pipes.
4. If you want to reduce the overall length of the fitting it is essential that this is done before the fitting is mounted to the ceiling, or connected to the mains supply. Unscrew the adjustable chain link (E), and adjust until the desired length is reached. The cable must now be shortened and the excess cable cut and re-connected to the terminal block. **NOTE: The electric cable must always be longer than the stem to prevent strain being placed on the cable. If you are unsure about your ability to do this, we recommend you contact a qualified electrician.**

## Assembly / User Instructions Continued

- Support your fitting and connect the house wiring to the terminal block – see expanded wiring details below.  
**NOTE: This is a Class II fitting and must NOT be earthed. Ensure no loose strands are left out of the connection block.**
- Secure the ceiling cup over the bracket (D) by using the screws (B) removed in Point 2.
- Fit the bulbs. **NOTE: Never fit bulbs of a higher wattage than those specified on the label (as these may cause over heating and damage the fitting).**
- The glass shade (H) and metal parts (G) are pre-assembled. Install the glass shade to the metal top (F) according to the installation drawing.
- Turn on the power and test.

